



6200lu Bearing 2D drawings and 3D CAD models

NTN 6200lu Bearing

Bearing No. 6200lu

Size	10x30x9 mm
Bore Diameter	10,000 mm
Outer Diameter	30,000 mm
Width	9,000 mm
d	10,000 mm
D	30,000 mm
B	9,000 mm
C	9,000 mm
rs min	0.6 mm
Radial clearance class	CN
Mass	0.03 kg
Dynamic load, C	5.1 kN
Static load, C0	2.39 kN
Fatigue limit load, Cu	0.11 kN
f0	13.2
Nlim (grease)	18,000 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPF1	4.93 Hz



CONSOLIDATED BEARING JAPAN LTD

da min	14 mm
da max	16 mm
Da max	26 mm
ra max	0.6 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.031
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 30MM Outside Diameter; 9MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com



CONSOLIDATED BEARING JAPAN LTD

Manufacturer Item Number	6200LU
Weight / LBS	0.071
Outer Race Width	0.354 Inch 9 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Bore	0.394 Inch 10 Millimeter
bore diameter:	10 mm
precision rating:	ISO Class 0
outside diameter:	30 mm
finish/coating:	Uncoated
overall width:	9 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	9 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	18000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	30000 RPM
dynamic load capacity:	5100 N
series:	62
static load capacity:	2390 N
manufacturer product page:	Click here